



Specifications Noxion LED Downlight Apollo 20W 2300lm 60D - 830 Warm White | 220mm - Cutout 200mm - Alu Reflector - UGR <19



[View Product](#)

General Information

| | |
|----------------------|---|
| SKU | 243082 |
| EAN | 8719157035019 |
| Manufacturer Code | 8719157035019 |
| Brand | Noxion |
| Manufacturer Name | Noxion LED Downlight Apollo 20W 2300LM 3000K Cutout Ø200mm Frame Ø220mm Alu Reflector |
| Budgetlight warranty | 6 Years |
| Average Lifetime (h) | 60000 |

Technical Information

| | |
|-----------------------------|----------------|
| Emergency Lighting | No |
| Tiltable | No |
| Technology | LED Integrated |
| Replaces (Watt) | 45 |
| Wattage | 20W |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 |
| Colour temperature (Kelvin) | 3000 |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |

| | |
|-------------------------|--------------------|
| Light Colour Options | Single Color |
| Including bulb | Yes |
| Inclusief Driver | Yes |
| Beam Angle (degree) | 60 |
| Luminous Flux (Lumen) | 2500lm |
| Lumen per watt | 125 |
| Powerfactor | >0.90 |
| Installation Depth (mm) | 140 |
| Unified Glare Rating | < 19 - For offices |
| Optische Afdekking | PC (Polycarbonate) |
| Afwerking Reflector | Aluminium |
| Type product | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 200 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Bedrijfstemperatuur | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Product Serie | Apollo |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 141 |
| Diameter (mm) | 220 |

Sensor Information

Type of sensor

No Sensor

Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**



Easy return process



Long-life **LED solutions**