



Specifications Noxion LED Downlight Apollo V2.0 15-25W 1800-3060lm 60D - 830/840 CCT | 220mm - Cutout 200mm

[View Product](#)

General Information

| | |
|----------------------|---|
| SKU | 248327 |
| EAN | 8719157046411 |
| Manufacturer Code | 8719157046411 |
| Brand | Noxion |
| Manufacturer Name | Noxion LED Downlight Apollo V2.0 15/20/25W MAX 2960lm 2CCT Cutout Ø200mm Frame Ø220mm Alu |
| Budgetlight warranty | 6 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|----------------|
| Tiltable | No |
| Technology | LED Integrated |
| Replaces (Watt) | 48 |
| Wattage | 25W |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830, 840 |
| Colour temperature (Kelvin) | 3000, 4000 |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light Colour Options | CCT |

| | |
|-----------------------|--------------------|
| Beam Angle (degree) | 60 |
| Luminous Flux (Lumen) | 2960lm |
| Lumen per watt | 124 |
| Powerfactor | >0.90 |
| Unified Glare Rating | < 19 - For offices |
| Optische Afdekking | PC (Polycarbonate) |
| Afwerking Reflector | Aluminium |
| Type product | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 200 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Bedrijfstemperatuur | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | PI [Push-in connector 2-pole] |
| Product Serie | Apollo |

Dimensions

Height (mm)

Why Budgetlight?

141

Diameter (mm)

220



Guaranteed **budget prices**



Up to **7 years warranty**

Sensor Information



Easy return process



Long-life **LED solutions**

Type of sensor

No Sensor