



Specifications Multipack 4x Ledvance LED Downlight Slim Round DN155 12W 1020lm 120D - 840 Cool White | 169mm

[View Product](#)

General Information

| | |
|----------------------|---|
| SKU | 253045 |
| EAN | 8719157059411 |
| Manufacturer Code | 8719157059411 |
| Brand | Ledvance |
| Manufacturer Name | Multipack 4x DL SLIM DN155 12W/4000K WT IP20 LEDV |
| Budgetlight warranty | 3 Years |
| Average Lifetime (h) | 30000 |

Technical Information

| | |
|-----------------------------|----------------|
| Emergency Lighting | No |
| Tiltable | No |
| Technology | LED Integrated |
| Replaces (Watt) | 2x18 |
| Wattage | 12W |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 840 |
| Colour temperature (Kelvin) | 4000 |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |

| | |
|-----------------------|--------------------|
| Light Colour Options | Single Color |
| Beam Angle (degree) | 120 |
| Luminous Flux (Lumen) | 1020lm |
| Lumen per watt | 85 |
| Powerfactor | >0.50 |
| Unified Glare Rating | < 28 |
| Optische Afdekking | PC (Polycarbonate) |
| Type product | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 155 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Bedrijfstemperatuur | -20 to +50 |
| Housing | PC (Polycarbonate) |
| Colour of the Fixture | White |
| Fixture Connection | PI [Push-in connector 2-pole] |
| Product Serie | DOWNLIGHT SLIM |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 30 |
| Diameter (mm) | 169 |

Sensor Information  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor  **Easy return process**  No Sensor  Long-life **LED solutions**