



Specifications Noxion LED Downlight
Apollo V2.0 TRIAC Dimmable 15-25W
1800-3060lm 60D - 830/840 CCT |
220mm - Cutout 200mm

[View Product](#)

General Information

| | |
|----------------------|--|
| SKU | 262122 |
| EAN | 8719157086127 |
| Manufacturer Code | 8719157086127 |
| Brand | Noxion |
| Manufacturer Name | Noxion LED Downlight Apollo V2.0 25W MAX 2960lm 2CCT Cutout Ø200mm Frame Ø220mm Alu TRIAC dimmable |
| Budgetlight warranty | 6 Years |
| Average Lifetime (h) | 100000 |

Technical Information

| | |
|-----------------------------|----------------|
| Tiltable | No |
| Technology | LED Integrated |
| Replaces (Watt) | 48 |
| Wattage | 25W |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable |
| Colour Code | 830, 840 |
| Colour temperature (Kelvin) | 3000, 4000 |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light Colour Options | CCT |

| | |
|-----------------------|--------------------|
| Beam Angle (degree) | 60 |
| Luminous Flux (Lumen) | 2960lm |
| Lumen per watt | 124 |
| Powerfactor | >0.90 |
| Unified Glare Rating | < 19 - For offices |
| Optische Afdekking | PC (Polycarbonate) |
| Afwerking Reflector | Aluminium |
| Type product | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 200 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Bedrijfstemperatuur | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Fixture Connection | PI [Push-in connector 2-pole] |
| Product Serie | Apollo |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 141 |
| Diameter (mm) | 220 |

Sensor Information  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor  **Easy** return process  No Sensor  Long-life **LED solutions**